



SAFETY DATA SHEET

FIXT 400 Bulk

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name FIXT 400 Bulk
 Product number FX081402

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Lubricant.

1.3. Details of the supplier of the safety data sheet

Supplier Seymour Road
 Nuneaton
 Warwickshire
 CV11 4LB

 02476 322 196 (T)
 02476 322 117 (F)
 info@fixtconsumables.com

1.4. Emergency telephone number

Emergency telephone 02476 322 196

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Not Classified
 Health hazards Asp. Tox. 1 - H304
 Environmental hazards Aquatic Chronic 3 - H412

Classification (67/548/EEC or 1999/45/EC) Xn;R65. R52/53,R66.

Human health Prolonged skin contact may cause redness and irritation. Gas or vapour in high concentrations may irritate the respiratory system.

Environmental The product contains a substance which may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements H304 May be fatal if swallowed and enters airways.
 H412 Harmful to aquatic life with long lasting effects.

FIXT 400 Bulk

Precautionary statements	P273 Avoid release to the environment. P102 Keep out of reach of children. P501 Dispose of contents/container in accordance with local regulations. P280 Wear protective gloves. P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P314 Get medical advice/attention if you feel unwell.
Supplemental label information	RCH002b For professional users only.
Contains	Odourless Kerosene

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Odourless Kerosene		60-100%
CAS number: —	EC number: 926-141-6	REACH registration number: 01-2119456620-43
Classification	Classification (67/548/EEC or 1999/45/EC)	
Asp. Tox. 1 - H304	Xn;R65. R66.	
Benzophenone		<1%
CAS number: 119-61-9	EC number: 204-337-6	REACH registration number: 01-2119899704-20
Classification	Classification (67/548/EEC or 1999/45/EC)	
STOT RE 2 - H373 Aquatic Chronic 2 - H411	N;R50/53.	
MONOCYCLIC TERPENE		<1%
CAS number: 5989-27-5	EC number: 227-813-5	REACH registration number: 01-2119529223-47
M factor (Acute) = 1	M factor (Chronic) = 1	
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226 Skin Sens. 1 - H317 Skin Irrit. 2 - H315 Aquatic Chronic 1 - H410 Aquatic Acute 1 - H400	Xn;R65. Xi;R38. N;R50/53. R10,R43.	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Remove affected person from source of contamination.
Inhalation	Move affected person to fresh air at once. Get medical attention if any discomfort continues.

FIXT 400 Bulk

Ingestion	Rinse mouth thoroughly with water. DO NOT induce vomiting. Get medical attention immediately.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Rinse with water. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
----------------------------	---

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with foam, carbon dioxide, dry powder or water fog.
-------------------------------------	--

5.2. Special hazards arising from the substance or mixture

Specific hazards	Toxic gases or vapours.
-------------------------	-------------------------

5.3. Advice for firefighters

Protective actions during firefighting	Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.
---	---

Special protective equipment for firefighters	Use protective equipment appropriate for surrounding materials.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Provide adequate ventilation. Avoid inhalation of vapours and contact with skin and eyes.
-----------------------------	---

6.2. Environmental precautions

Environmental precautions	Do not discharge into drains or watercourses or onto the ground.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Absorb in vermiculite, dry sand or earth and place into containers.
--------------------------------	---

6.4. Reference to other sections

Reference to other sections	For personal protection, see Section 8. For waste disposal, see Section 13.
------------------------------------	---

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions	Read and follow manufacturer's recommendations.
--------------------------	---

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions	Store in tightly-closed, original container in a dry, cool and well-ventilated place.
----------------------------	---

7.3. Specific end use(s)

Specific end use(s)	The identified uses for this product are detailed in Section 1.2.
----------------------------	---

FIXT 400 Bulk

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Odourless Kerosene

Long-term exposure limit (8-hour TWA): OEL 1200 mg/m³

MONOCYCLIC TERPENE

Long-term exposure limit (8-hour TWA): No std.

OEL = Occupational Exposure Limit.

Ingredient comments WEL = Workplace Exposure Limits SUP = Supplier's recommendation.

8.2. Exposure controls

Appropriate engineering controls Provide adequate ventilation. Avoid inhalation of vapours and spray/mists. Observe any occupational exposure limits for the product or ingredients.

Personal protection When using do not smoke.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. Polyvinyl alcohol (PVA). Viton rubber (fluoro rubber). The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.

Hygiene measures Wash hands after handling. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Use appropriate hand lotion to prevent defatting and cracking of skin.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Amber.
Odour	Hydrocarbons.
Initial boiling point and range	190 - 280°C @ 1013 hPa
Flash point	70°C
Evaporation rate	600 (diethyl ether = 1)
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 0.5% Upper flammable/explosive limit: 6%
Vapour pressure	0.15 hPa @ 20°C
Vapour density	> 1
Relative density	0.8 @ °C
Solubility(ies)	Immiscible with water.
Auto-ignition temperature	>200°C

FIXT 400 Bulk

Viscosity	<3 cSt @ 40°C
Comments	Information given is applicable to the major ingredient.

9.2. Other information

Other information	Not available.
Volatile organic compound	This product contains a maximum VOC content of 805 g/l.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Stable at normal ambient temperatures and when used as recommended.
-------------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Does not decompose when used and stored as recommended.
---	---

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition.
----------------------------	---

10.5. Incompatible materials

Materials to avoid	Keep away from oxidising materials, heat and flames.
---------------------------	--

10.6. Hazardous decomposition products

Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapours.
---	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General information	This product has low toxicity. Only large quantities are likely to have adverse effects on human health.
Inhalation	Gas or vapour in high concentrations may irritate the respiratory system.
Skin contact	Repeated exposure may cause skin dryness or cracking.
Eye contact	Vapour or spray in the eyes may cause irritation and smarting.
Acute and chronic health hazards	Irritating to skin. Contents may cause lung damage if swallowed. Aspiration into the lungs may cause chemical pneumonitis. In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea.
Route of entry	Skin and/or eye contact
Target organs	Skin Eyes
Medical symptoms	Skin irritation.

SECTION 12: Ecological Information

Ecotoxicity	The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.
--------------------	--

FIXT 400 Bulk

12.1. Toxicity

Toxicity Not available.

12.2. Persistence and degradability

Persistence and degradability Not available.

12.3. Bioaccumulative potential

Bioaccumulative potential Not available.

12.4. Mobility in soil

Mobility Not known.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment Not available.

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

Transport labels

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

FIXT 400 Bulk

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
EU legislation	Commission Regulation (EU) No 453/2010 of 20 May 2010.
Guidance	Workplace Exposure Limits EH40. CHIP for everyone HSG228. Safety Data Sheets for Substances and Preparations. Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments	Supplemental information added.
Revision date	16/09/2015
Revision	2
SDS number	12456
SDS status	Approved.
Risk phrases in full	R10 Flammable. R38 Irritating to skin. R43 May cause sensitisation by skin contact. R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 Harmful: may cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking.
Hazard statements in full	H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H400 Very toxic to aquatic life. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H410 Very toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.