

Safety Data Sheet according to (EC) No 1907/2006

Page 1 of 9

SDS No.: 328944

V003.3

Revision: 28.08.2015

printing date: 08.08.2016

Replaces version from: 25.06.2014

DOUBLE BUBBLE MIX & FIX EPOXY KITS

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier 865275 & 865279 DOUBLE BUBBLE MIX & FIX EPOXY KITS

Contains:

RP Bisphenol F-epichlorohydrin resin, MW<=700 Trimethylolpropane triglycidyl ether

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Part A of 2-K-Epoxy Adhesive

1.3. Details of the supplier of the safety data sheet

Quest Consumables Ltd Stock House ,Seymour Road Nuneaton, Warwickshire CV11 4LB

Phone: +44 2476322126 Fax-no.: +44 2476322117 sales@questconsumables.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin irritation Category 2

H315 Causes skin irritation.

Serious eye irritation Category 2

H319 Causes serious eye irritation.

Skin sensitizer Category 1

H317 May cause an allergic skin reaction.

Chronic hazards to the aquatic environment Category 2

H411 Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements (CLP):

V003.3

Hazard pictogram:



Signal word: Warning

Hazard statement: H315 Causes skin irritation.

> H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statement: P273 Avoid release to the environment.

P280 Wear protective gloves. Prevention

P302+P352 IF ON SKIN: Wash with plenty of water. **Precautionary statement:**

P333+P313 If skin irritation or rash occurs: Get medical advice/attention. Response

P337+P313 If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

None if used properly.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General chemical description:

Part A of two part adhesive

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components	EC Number	content	Classification
CAS-No.	REACH-Reg No.		
RP Bisphenol F-epichlorohydrin resin,	01-2119454392-40	50- 100 %	Skin Irrit. 2
MW<=700			H315
28064-14-4			Skin Sens. 1
			H317
			Aquatic Chronic 2
			H411
Trimethylolpropane triglycidyl ether		20- 40 %	Skin Irrit. 2; Dermal
30499-70-8			H315
			Skin Sens. 1; Dermal
			H317
			Eye Irrit. 2
			H319
			Aquatic Chronic 3
			H412

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

MSDS-No.: 328944 Page 3 of 9 V003.3

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Rash, Urticaria.

EYE: Irritation, conjunctivitis.

SKIN: Redness, inflammation.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

None known

5.2. Special hazards arising from the substance or mixture

Oxides of carbon.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Wear protective equipment.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid skin and eye contact.

6.2. Environmental precautions

Do not let product enter drains.

Waste disposal with the approval of the responsible local authority.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Wash spillage site thoroughly with soap and water or detergent solution.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

The normal precautions for dealing with chemical products should be taken.

Avoid skin and eye contact.

Hygiene measures:

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

Good industrial hygiene practices should be observed.

Page 4 of 9

MSDS-No.: 328944

V003.3

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container.

Store in a cool, dry place.

7.3. Specific end use(s)

Part A of 2-K-Epoxy Adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Great Britain

None

Occupational Exposure Limits

Valid for

Ireland

None

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Skin protection:

Wear suitable protective clothing.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance liquid colourless

Odor Slight

Odour threshold No data available / Not applicable

pH No data available / Not applicable

 $\begin{array}{ll} \text{Initial boiling point} & > 200 \,^{\circ}\text{C} \; (> 392 \,^{\circ}\text{F}) \\ \text{Flash point} & > 100,00 \,^{\circ}\text{C} \; (> 212 \,^{\circ}\text{F}) \end{array}$

Decomposition temperature

Vapour pressure

No data available / Not applicable

No data available / Not applicable

Density 1,2000 g/cm3

()

Bulk density No data available / Not applicable

Viscosity 60.000,00 mPa.s

()

Viscosity (kinematic) No data available / Not applicable No data available / Not applicable Explosive properties Solubility (qualitative) No data available / Not applicable Solidification temperature No data available / Not applicable No data available / Not applicable Melting point No data available / Not applicable Flammability Auto-ignition temperature No data available / Not applicable Explosive limits No data available / Not applicable No data available / Not applicable Partition coefficient: n-octanol/water Evaporation rate No data available / Not applicable Vapor density No data available / Not applicable No data available / Not applicable Oxidising properties

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Reaction with strong bases Reaction with strong acids. Avoid contact with amines. Reaction with strong oxidants.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

carbon oxides.

V003.3

MSDS-No.: 328944

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Oral toxicity:

May cause irritation to the digestive tract.

Skin irritation:

Causes skin irritation.

Eye irritation:

Causes serious eye irritation.

Sensitizing:

May cause an allergic skin reaction.

Acute oral toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
RP Bisphenol F- epichlorohydrin resin, MW<=700	LD50	> 5.000 mg/kg	oral		rat	OECD Guideline 401 (Acute Oral Toxicity)
28064-14-4 Trimethylolpropane triglycidyl ether 30499-70-8	LD50	> 2.000 mg/kg	oral			

Acute dermal toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Trimethylolpropane	LD50	> 2.000 mg/kg	dermal		rat	
triglycidyl ether						
30499-70-8						

Serious eye damage/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
RP Bisphenol F-	not irritating		rabbit	OECD Guideline 405 (Acute
epichlorohydrin resin,				Eye Irritation / Corrosion)
MW<=700				-
28064-14-4				

SECTION 12: Ecological information

General ecological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

12.1. Toxicity

Ecotoxicity:

Toxic to aquatic life with long lasting effects.

Do not empty into drains / surface water / ground water.

MSDS-No.: 328944

V003.3

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
RP Bisphenol F- epichlorohydrin resin, MW<=700 28064-14-4	EC50	3,5 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

12.2. Persistence and degradability

Persistence and Biodegradability:

The product is not biodegradable.

	Hazardous components	Result	Route of	Degradability	Method
	CAS-No.		application		
ſ	RP Bisphenol F-		aerobic	10 - 16 %	OECD Guideline 301 B (Ready
	epichlorohydrin resin,				Biodegradability: CO2 Evolution
	MW<=700				Test)
	28064-14-4				

12.3. Bioaccumulative potential / 12.4. Mobility in soil

Cured adhesives are immobile.

Bioaccumulative potential:

No data available for the product.

12.5. Results of PBT and vPvB assessment

Hazardous components	PBT/vPvB
CAS-No.	
RP Bisphenol F-epichlorohydrin resin,	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
MW<=700	Bioaccumulative (vPvB) criteria.
28064-14-4	

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

MSDS-No.: 328944

SECTION 14: Transport information

14.1. UN number

ADR	3082
RID	3082
ADN	3082
IMDG	3082
IATA	3082

14.2. UN proper shipping name

ADR	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)
RID	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)
ADN	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy

IATA Environmentally hazardous substance, liquid, n.o.s. (Epoxy resin)

14.3. Transport hazard class(es)

ADR	9
RID	9
ADN	9
IMDG	9
IATA	9

14.4. Packing group

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	Marine pollutant
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable
	Tunnelcode: (E)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

MSDS-No.: 328944

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Label elements (DPD):

Xi - Irritant

N - Dangerous for the environment





Risk phrases:

R36/38 Irritating to eyes and skin.

R43 May cause sensitisation by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases:

- S24 Avoid contact with skin.
- S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- S28 After contact with skin, wash immediately with plenty of water and soap.
- S37 Wear suitable gloves.
- S61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

Additional labeling:

Contains epoxy constituents. See information supplied by the manufacturer.

Contains:

RP Bisphenol F-epichlorohydrin resin, MW<=700,

Trimethylolpropane triglycidyl ether

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.