

## Soldering Flux Paste

Revision 2

Revision date 2015-06-19

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	845114
Product name	Soldering Flux Paste
<b>1.3. Details of the supplier of the safety data sheet</b>	
Company	Quest Consumables Ltd
Address	Stock House, Seymour Road Nuneaton, Warwickshire CV11 4LB United Kingdom Sales@questconsumables.com
Web	
Telephone	+44 (0) 2476 322126
Fax	+44 (0) 2476 322117
Email	+sales@questconsumables.com

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/EC	N; R51/53 Symbols: N: Dangerous for the environment.
Main hazards	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### 67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Zinc chloride (Zinc chloride, fume)	030-003-00-2	7646-85-7	231-592-0		1 - 10%	C; R34 Xn; R22 N; R50/53	
Ammonium chloride (Ammonium chloride, fume)	017-014-00-8	12125-02-9	235-186-4		0 - 0.5%	Xn; R22 Xi; R36	

##### EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Zinc chloride (Zinc chloride, fume)	030-003-00-2	7646-85-7	231-592-0		1 - 10%	Acute Tox. 4: H302; Skin Corr. 1B: H314; Aquatic Acute 1: H400; Aquatic Chronic 1: H410;	

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

Inhalation	Toxic by inhalation. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Inhalation of vapour may cause shortness of breath. Move the exposed person to fresh air. Seek medical attention.
------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

# Soldering Flux Paste

Revision 2

Revision date 2015-06-19

## 4.1. Description of first aid measures

Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Toxic in contact with skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention.
Ingestion	Toxic if swallowed. Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. If swallowed, seek medical advice immediately and show this container or label. DO NOT INDUCE VOMITING.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

	Carbon oxides. Alcohol resistant foam.
--	----------------------------------------

### 5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---------------------------------------------------------

### 5.3. Advice for firefighters

	Wear: Self-contained breathing apparatus. Wear chemical protective clothing.
--	------------------------------------------------------------------------------

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Evacuate personnel to a safe area. Wear suitable protective equipment.
--	-------------------------------------------------------------------------------------------------------------------------

### 6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	-------------------------------------------------------------------------

### 6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	-----------------------------------------------------------------------------------------------------------------------------------------------------

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area.
--	------------------------------------------------------------------------------------

### 7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed.
--	----------------------------------------------------------------------------

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1. Exposure Limit Values

# Soldering Flux Paste

Revision 2

Revision date 2015-06-19

## 8.1.1. Exposure Limit Values

Ammonium chloride (Ammonium chloride, fume)	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: 10
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: 20
	WEL 8-hr limit mg/m3 total inhalable dust: -	WEL 15 min limit mg/m3 total inhalable dust: -
	WEL 8-hr limit mg/m3 total respirable dust: -	WEL 15 min limit mg/m3 total respirable dust: -
Zinc chloride (Zinc chloride, fume)	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: 1
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: 2
	WEL 8-hr limit mg/m3 total inhalable dust: -	WEL 15 min limit mg/m3 total inhalable dust: -
	WEL 8-hr limit mg/m3 total respirable dust: -	WEL 15 min limit mg/m3 total respirable dust: -

## 8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	Self-contained breathing apparatus must be used in handling.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	Gel
Colour	Brown
Odour	Mild

## SECTION 10: Stability and reactivity

### 10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

## SECTION 11: Toxicological information

### 11.1.4. Toxicological Information

	No data is available on this product.
--	---------------------------------------

## SECTION 12: Ecological information

### 12.1. Toxicity

	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
--	---------------------------------------------------------------------------------------------

## SECTION 13: Disposal considerations

### General information

	Dispose of in compliance with all local and national regulations.
--	-------------------------------------------------------------------

## SECTION 14: Transport information

### Further information

	The product is not classified as dangerous for carriage.
--	----------------------------------------------------------

## SECTION 15: Regulatory information

# Soldering Flux Paste

Revision 2

Revision date 2015-06-19

## SECTION 16: Other information

### Other information

Revision	<p>This document differs from the previous version in the following areas:.</p> <p>2 - 2.1. Classification of the substance or mixture.</p> <p>12 - 12.1. Toxicity.</p> <p>15 - Labelling.</p> <p>15 - Risk phrases.</p> <p>15 - Safety phrases.</p>
Text of risk phrases in Section 3	<p>R22 - Harmful if swallowed.</p> <p>R34 - Causes burns.</p> <p>R36 - Irritating to eyes.</p> <p>R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.</p>
Text of Hazard Statements in Section 3	<p>Acute Tox. 4: H302 - Harmful if swallowed.</p> <p>Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.</p> <p>Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.</p>

### Further information

	<p>The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.</p>
--	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------