

**SAFETY DATA SHEET**  
**KIND TRAFFIC FILM REMOVER**

Page: 1

Compilation date: 14/04/2020

Revision No: 4.01

**Section 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

Product name: KIND TRAFFIC FILM REMOVER

Product code: LC213

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Use of substance / mixture: PC35: Washing and cleaning products (including solvent based products).

**1.3. Details of the supplier of the safety data sheet**

Company name: Car-Chem Ltd

Unit 1

Park Road East

Calverton

Nottinghamshire

NG14 6LL

United Kingdom

Tel: +44 (0) 844 414 0987

Email: info@car-chem.co.uk

**1.4. Emergency telephone number**

Emergency tel: +44 (0) 844 414 0987

**Section 2: Hazards identification**

**2.1. Classification of the substance or mixture**

Classification under CLP: Eye Dam. 1: H318; Skin Irrit. 2: H315

Most important adverse effects: Causes skin irritation. Causes serious eye damage.

**2.2. Label elements**

Label elements:

Hazard statements: H315: Causes skin irritation.

H318: Causes serious eye damage.

Hazard pictograms: GHS05: Corrosion



Signal words: Danger

Precautionary statements: P264: Wash hands thoroughly after handling.

P280: Wear <protective gloves/protective clothing/eye protection/face protection>.

P302+352: IF ON SKIN: Wash with plenty of water/soap

[cont...]

**SAFETY DATA SHEET**  
**KIND TRAFFIC FILM REMOVER**

Page: 2

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes.  
Remove contact lenses, if present and easy to do. Continue rinsing.  
P310: Immediately call a <POISON CENTER/doctor/POISON CENTER/doctor>.  
P321: Specific treatment (see instructions on this label).

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

TETRASODIUM ETHYLENE DIAMINE TETRAACETATE - REACH registered number(s): 01-2119486762-27-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
200-573-9	64-02-8	-	Acute Tox. 4: H302; Eye Dam. 1: H318	1-10%

SODIUM HYDROXIDE - REACH registered number(s): 01-2119457892-27-XXXX

215-185-5	1310-73-2	-	Skin Corr. 1A: H314	1-10%
-----------	-----------	---	---------------------	-------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

[cont...]

**SAFETY DATA SHEET**  
**KIND TRAFFIC FILM REMOVER**

**Section 5: Fire-fighting measures**

**5.1. Extinguishing media**

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

**5.2. Special hazards arising from the substance or mixture**

Exposure hazards: In combustion emits toxic fumes.

**5.3. Advice for fire-fighters**

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

**Section 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised personnel.  
Do not attempt to take action without suitable protective clothing - see section 8 of SDS.  
Turn leaking containers leak-side up to prevent the escape of liquid.

**6.2. Environmental precautions**

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

**6.3. Methods and material for containment and cleaning up**

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

**6.4. Reference to other sections**

Reference to other sections: Refer to section 8 of SDS.

**Section 7: Handling and storage**

**7.1. Precautions for safe handling**

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.  
Avoid the formation or spread of mists in the air.

**7.2. Conditions for safe storage, including any incompatibilities**

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.  
Suitable packaging: It is recommended to store in original packaging

**7.3. Specific end use(s)**

Specific end use(s): PC35: Washing and cleaning products (including solvent based products).

**Section 8: Exposure controls/personal protection**

**8.1. Control parameters**

**SAFETY DATA SHEET**  
**KIND TRAFFIC FILM REMOVER**

Hazardous ingredients:

SODIUM HYDROXIDE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	-	2 mg/m <sup>3</sup>	-	-

**DNEL/PNEC Values**

DNEL / PNEC No data available.

**8.2. Exposure controls**

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Gloves (alkali-resistant). Gloves should be replaced regularly or if any change in appearance is noticed. Ensure gloves are manufactured/tested in accordance with BS EN 374. Penetration times carried out according to EN 374 part III are not always practical, therefore max. wearing time of 50% of penetration time is recommended.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: An environmental assessment must be made to ensure compliance with local environmental legislation.

**Section 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

State: Liquid

Solubility in water: Soluble

Viscosity: Non-viscous

Flash point°C: >100

**9.2. Other information**

Other information: No data available.

**Section 10: Stability and reactivity**

**10.1. Reactivity**

Reactivity: Stable under recommended transport or storage conditions.

**10.2. Chemical stability**

Chemical stability: Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

**SAFETY DATA SHEET**  
**KIND TRAFFIC FILM REMOVER**

Page: 5

**10.4. Conditions to avoid**

Conditions to avoid: Heat.

**10.5. Incompatible materials**

Materials to avoid: Strong oxidising agents. Strong acids.

**10.6. Hazardous decomposition products**

Haz. decomp. products: In combustion emits toxic fumes.

**Section 11: Toxicological information**

**11.1. Information on toxicological effects**

Hazardous ingredients:

SODIUM HYDROXIDE

IPR	MUS	LD50	40	mg/kg
ORL	RBT	LDLO	500	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

**Symptoms / routes of exposure**

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

**Section 12: Ecological information**

**12.1. Toxicity**

Ecotoxicity values: No data available.

**12.2. Persistence and degradability**

Persistence and degradability: No data available.

**12.3. Bioaccumulative potential**

Bioaccumulative potential: No data available.

[cont...]

**SAFETY DATA SHEET**  
**KIND TRAFFIC FILM REMOVER**

Page: 6

**12.4. Mobility in soil**

Mobility: No data available.

**12.5. Results of PBT and vPvB assessment**

PBT identification: This product is not identified as a PBT/vPvB substance.

**12.6. Other adverse effects**

Other adverse effects: Negligible ecotoxicity.

**Section 13: Disposal considerations**

**13.1. Waste treatment methods**

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**Section 14: Transport information**

Transport class: This product does not require a classification for transport.

**Section 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Specific regulations: EU Legislation Regulation (EC) No 1907/2006 REACH. Regulation (EC) No 1272/2008 CLP. Guidance Notes: Workplace Exposure Limits EH40 This mixture may be classed as a detergent due to its intended use and we expect it to comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents, based on details of the individual chemicals.

**15.2. Chemical Safety Assessment**

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

**Section 16: Other information**

**Other information**

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

Phrases used in s.2 and s.3: H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H318: Causes serious eye damage.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

[final page]